



Consumer Information Card
ENERGY CONTROL, INC. — Ossian, Indiana

Revised 7/27/17
 Code: 37514PS

The Manufacturer recommends that Forest-Wool Cellulose Insulation be installed in accordance with each of the following chart minimums to provide the thermal resistance (R-Values) listed.

PNEUMATIC APPLICATION RECOMMENDATIONS — Forest-Wool Insulation (25# Bag)

	R-Value @ 75°	Initial Installed Thickness (in.)	Minimum Settled Thickness (in.)	Framing: 2x6 @ 16 in. OC		Framing: None
				Maximum Net Coverage (ft ² /bag)	Bags per 1,000 ft ²	Minimum Weight (lbs/ft ²)
ATTIC	13	4.2	3.8	79.8	12.5	0.35
	19	5.9	5.3	49.8	20.1	0.55
	22	6.8	6.1	41.4	24.2	0.66
	23	7.1	6.4	39.1	25.5	0.69
	27	8.2	7.4	32.1	31.1	0.84
	30	9.1	8.2	28.3	35.3	0.94
	35	10.5	9.5	23.6	42.4	1.12
	38	11.4	10.3	21.4	46.6	1.23
	40	12.0	10.8	20.2	49.5	1.30
	42	12.6	11.3	19.1	52.3	1.37
	46	13.7	12.4	17.3	58.0	1.51
	49	14.6	13.1	16.1	62.2	1.62
	50	14.9	13.4	15.7	63.6	1.65
	54	16.1	14.4	14.4	69.3	1.80
	55	16.3	14.7	14.1	70.8	1.83
	57	16.9	15.2	13.6	73.6	1.90
60	17.8	16.0	12.8	77.9	2.01	
SIDE WALL	13.3	3.5	3.5	<i>This bag will cover 30.0 sq. ft. in 2x4 closed sidewall</i>		
	21	5.5	5.5	<i>This bag will cover 19.0 sq. ft. in 2x6 closed sidewall</i>		

BUILDER'S AND APPLICATOR'S CERTIFICATION

This is to certify that Forest-Wool brand Cellulose Insulation has been installed in conformance with the above specifications to provide a thermal resistance of R-_____ using _____ bags of FW 25# bags to cover _____ square feet of living area, and R-_____ using _____ bags to cover _____ square feet of garage ceiling. BAG DATE _____

Date _____ Company Name _____ Applicator's Signature _____
 Date _____ Company Name _____ Builder's Signature _____

Forest-Wool Insulation Complies with Federal Specifications HH-1-515D & ASTM C-739-03 and ASTM C1374.
 All heat sources including (but not limited to) recessed lights, fireplace, furnace and water heater flues have been wrapped in such a way as to prevent cellulose insulation from coming in contact with metal flue or light.

(signature)